

TSAH0630

IP68 Side Opening Die-cast Aluminum Camera Housing

Die-cast aluminum construction, bundled internal cable managed bracket, internal usable size (W × H × L): 100 mm × 80 mm × 335 mm



Features

- IP68, NEMA-6P enclosure rating
- Designed for indoor and outdoor applications
- Input power: 12 V DC/24 V AC/220 V AC (available) or PoE (upgradable)
- Built-in heater and blower (optional)
- Adjustable sliding camera tray
- Cable entry glands and mounting holes on bottom of housing
- Die-cast aluminum construction
- High impact resistance
- Hinged side opening for easy installation and camera setup
- Bundled internal cable managed bracket

Available Models

Model	Heater	Blower	Input Power
TSAH0630			
TSAH0631-1	+		12 V DC
TSAH0631-2	+		24 V AC
TSAH0631-4	+		220 V AC
TSAH0633-1	+	+	12 V DC
TSAH0633-2	+	+	24 V AC
TSAH0633-4	+	+	220 V AC
TSAH0630-5			PoE
TSAH0631-5	+		PoE
TSAH0633-5	+	+	PoE
TSAH0633-9	+	+	PoE

Tech Specs

Model	TSAH0630
Type	Indoor/Outdoor, side opening
Protection Rating	IP68, NEMA-6P enclosure rating
Material	Die-cast aluminum
Finish	White polyester powder coat
Input Power	<ul style="list-style-type: none"> • 12 V DC (TSAH0631-1, TSAH0633-1) • 24 V AC (TSAH0631-2, TSAH0633-2) • 220 V AC (TSAH0631-4, TSAH0633-4) • PoE (IEEE 802.3at Class 4 PoE Plus compliant) (TSAH0630-5, TSAH0631-5, TSAH0633-5) • PoE (48 V DC) (TSAH0633-9)
Power Consumption	<ul style="list-style-type: none"> • Heater (24 V AC): 6 W (250 mA) • Heater (220 V AC): 5.3 W (23 mA) • Heater (12 V DC): 4.2 W (350 mA) • Blower: 1.68 W (140 mA)
Network Interface	<ul style="list-style-type: none"> • RJ-45 × 2 (PoE input/data output) (TSAH0630-5, TSAH0631-5, TSAH0633-5) • RJ-45 × 2 (PoE input/PoE output) (TSAH0633-9)
Dimensions (W × H × L)	145 mm × 109 mm × 406 mm (5.71 in × 4.29 in × 15.98 in)
Window Viewing Area (W × H)	92 mm × 76 mm (3.62 in × 2.99 in)
Window Thickness	3 mm (0.12 in), tempered glass
Internal Usable Size (W × H × L)	<ul style="list-style-type: none"> • 100 mm × 80 mm × 335 mm (3.94 in × 3.15 in × 13.19 in) (TSAH0630) • 100 mm × 80 mm × 250 mm (3.94 in × 3.15 in × 9.84 in) (TSAH0631-1, TSAH0631-2, TSAH0631-4, TSAH0633-1, TSAH0633-2, TSAH0633-4, TSAH0633-9) • 100 mm × 80 mm × 280 mm (3.94 in × 3.15 in × 11.02 in) (TSAH0630-5, TSAH0631-5, TSAH0633-5)
Heater Control	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (TSAH0631-1, TSAH0631-2, TSAH0631-4, TSAH0633-1, TSAH0633-2, TSAH0633-4, TSAH0631-5, TSAH0633-5, TSAH0633-9)
Blower Control	On at 40 °C ± 3 °C (104 °F ± 5 °F), off at 30 °C ± 3 °C (86 °F ± 5 °F) (TSAH0633-1, TSAH0633-2, TSAH0633-4, TSAH0633-5, TSAH0633-9)
Operating Ambient Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Related Products	<ul style="list-style-type: none"> • TSAM0165: Cable and Adaptor Managed Wall Housing Bracket • TSAM0187: Cable Managed Pendant Mount Bracket • TSAM0308: Pole Mount Bracket • TSAI0510: IP68 LED 20 m to 40 m Illuminator
Weight	3.6 kg (7.94 lb)
Certifications	CE, FCC, RoHS

*Design and specifications are subject to change without prior notice.