

## TSAH0630

### IP68 Side Opening Die-cast Aluminum Camera Housing

Die-cast aluminum construction, bundled internal cable managed bracket, internal usable size (W × H × L): 100 mm × 80 mm × 335 mm



### Features

- IP68, NEMA-6P enclosure rating
- Designed for indoor and outdoor applications
- Input power: 12 V DC/24 V AC/220 V AC (available) or PoE (upgradable)
- Built-in heater and blower (optional)
- Adjustable sliding camera tray
- Cable entry glands and mounting holes on bottom of housing
- Die-cast aluminum construction
- High impact resistance
- Hinged side opening for easy installation and camera setup
- Bundled internal cable managed bracket

### Available Models

Model	Heater	Blower	Input Power
TSAH0630			
TSAH0631-1	+		12 V DC
TSAH0631-2	+		24 V AC
TSAH0631-4	+		220 V AC
TSAH0633-1	+	+	12 V DC
TSAH0633-2	+	+	24 V AC
TSAH0633-4	+	+	220 V AC
TSAH0630-5			PoE
TSAH0631-5	+		PoE
TSAH0633-5	+	+	PoE
TSAH0633-9	+	+	PoE

### Tech Specs

Model	TSAH0630
<b>Type</b>	Indoor/Outdoor, side opening
<b>Protection Rating</b>	IP68, NEMA-6P enclosure rating
<b>Material</b>	Die-cast aluminum
<b>Finish</b>	White polyester powder coat
<b>Input Power</b>	<ul style="list-style-type: none"> <li>• 12 V DC (TSAH0631-1, TSAH0633-1)</li> <li>• 24 V AC (TSAH0631-2, TSAH0633-2)</li> <li>• 220 V AC (TSAH0631-4, TSAH0633-4)</li> <li>• PoE (IEEE 802.3at Class 4 PoE Plus compliant) (TSAH0630-5, TSAH0631-5, TSAH0633-5)</li> <li>• PoE (48 V DC) (TSAH0633-9)</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Heater (24 V AC): 6 W (250 mA)</li> <li>• Heater (220 V AC): 5.3 W (23 mA)</li> <li>• Heater (12 V DC): 4.2 W (350 mA)</li> <li>• Blower: 1.68 W (140 mA)</li> </ul>
<b>Network Interface</b>	<ul style="list-style-type: none"> <li>• RJ-45 × 2 (PoE input/data output) (TSAH0630-5, TSAH0631-5, TSAH0633-5)</li> <li>• RJ-45 × 2 (PoE input/PoE output) (TSAH0633-9)</li> </ul>
<b>Dimensions (W × H × L)</b>	145 mm × 109 mm × 406 mm (5.71 in × 4.29 in × 15.98 in)
<b>Window Viewing Area (W × H)</b>	92 mm × 76 mm (3.62 in × 2.99 in)
<b>Window Thickness</b>	3 mm (0.12 in), tempered glass
<b>Internal Usable Size (W × H × L)</b>	<ul style="list-style-type: none"> <li>• 100 mm × 80 mm × 335 mm (3.94 in × 3.15 in × 13.19 in) (TSAH0630)</li> <li>• 100 mm × 80 mm × 250 mm (3.94 in × 3.15 in × 9.84 in) (TSAH0631-1, TSAH0631-2, TSAH0631-4, TSAH0633-1, TSAH0633-2, TSAH0633-4, TSAH0633-9)</li> <li>• 100 mm × 80 mm × 280 mm (3.94 in × 3.15 in × 11.02 in) (TSAH0630-5, TSAH0631-5, TSAH0633-5)</li> </ul>
<b>Heater Control</b>	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (TSAH0631-1, TSAH0631-2, TSAH0631-4, TSAH0633-1, TSAH0633-2, TSAH0633-4, TSAH0631-5, TSAH0633-5, TSAH0633-9)
<b>Blower Control</b>	On at 40 °C ± 3 °C (104 °F ± 5 °F), off at 30 °C ± 3 °C (86 °F ± 5 °F) (TSAH0633-1, TSAH0633-2, TSAH0633-4, TSAH0633-5, TSAH0633-9)
<b>Operating Ambient Temperature</b>	-40 °C to 60 °C (-40 °F to 140 °F)
<b>Related Products</b>	<ul style="list-style-type: none"> <li>• TSAM0165: Cable and Adaptor Managed Wall Housing Bracket</li> <li>• TSAM0187: Cable Managed Pendant Mount Bracket</li> <li>• TSAM0308: Pole Mount Bracket</li> <li>• TSAI0510: IP68 LED 20 m to 40 m Illuminator</li> </ul>
<b>Weight</b>	3.6 kg (7.94 lb)
<b>Certifications</b>	CE, FCC, RoHS

\*Design and specifications are subject to change without prior notice.